

Datasheet Wellgrab 218 HPHT

By allowing reliable disconnect of fishing strings or relocating the fish in the well, the electric release fishing tool is designed to improve and simplify fishing operations. The required grapple type, either external or internal, can be easily assembled on the tool by only changing a few parts. Electrical disconnect can be activated at any time when required.

Applications	Features	Benefits
• Retrieving plugs	• Interchangeable stand-off rings and bell guides	• Prevents premature release of the equipment during fishing or retrieving
• Fishing operations	• Simple change-out grapples	• 50% higher safe working loads than for standard pulling tools
• Relocating downhole assemblies	• 5.7 ton capacity on release power	• Digital, real-time communication with fishing tool
• Heavy Duty fishing	• Electrical release command	• Operates on any e-line
• Surface controlled manipulation of downhole components	• Adjustable reach	• Eliminate uncertainties associated with shear pins and –screws
• Replace requirement for deployment BOP operations	• Bi-directional motor for grapple manipulation	• No need to swap between slickline and e-line
	• Fail-safe timer release device	

Specifications*	Imperial	Metric
• Length	• 6.06 ft	• 1847 mm
• Tool OD	• 2.125"	• 54 mm
• Weight in air	• 45 lbs	• 20.5 kg
• Completion ID range	• >2.275"	• >57.8 mm
• Grapple range – Fishing object size range	• 0.875" – 5.630" *	• 22 mm – 508 mm
• Safe working load	• 66 klbs	• 29.9 ton
• Max pressure rating	• 20 000 psi	• 1379 bar
• Temperature rating	• 350 °F	• 177 °C

* Dependent upon configuration and can be custom designed to different sizes

