

DATA SHEET WELL TRACTOR® 212

COILED TUBING

The original Well Tractor® was in fact a version designed to run on Coiled Tubing. Harnessing the fluids pumped from surface it is an essential tool for overcoming helical buckling or washouts, pulling the coiled tubing deeper into the wellbore. It is compatible with certain downhole tools allowing operators to pass coil and tools through small restrictions as well as operate in large diameter boreholes. Extend your reach with the CT Well Tractor®.

APPLICATIONS

- Stimulations
- Clean-out solutions
- Perforating
- Milling solutions
- Mechanical solutions
- Spotting pills
- Fishing
- Washing / displacing
- Fracturing

FEATURES

- Passive fail-safe system
- Modular
- Surface read-out
- Logging while tractoring
- Universal through wiring
- NACE compliant

BENEFITS

- Overcome buckling
- Prevents stuck tools
- Configurable
- Maximum efficiency
- Optimal data acquisition
- OH or CH applications
- Large range of ID's accessible



SPECIFICATIONS*

	IMPERIAL	METRIC
Length	14.5 ft	4.4 m
Running OD nominal	2 ½"	64 mm
Weight in air	370 lbs	168 Kg
OH / Completion ID range	2.6" – 10.1"	66.0 mm – 257 mm
Tandem force configuration	6,000 lbs @ 0.8 bbl/min	2700 Kg @ 127 l/min
Maximum flow rate	1.7 bbl/min	270 l/min
Maximum well pressure	25,000 psi	1,720 bar
Maximum well temperature	400 F	200 °C
Tensile strength	37,000 lbs	16,800 Kg
Compressive strength	44,000 lbs	20,000 Kg

*Dependent upon configuration