

## Datasheet Well Tractor® 212 CVT Continuous Variable Tractoring

The ultimate conveyance solution from our pioneering Well Tractor® range. The Continuous Variable Tractoring (CVT) system automatically maximizes speed and power at all times, optimizing every conveyance run, making operations faster and more efficient than ever before.

Applications	Features	Benefits
• Clean-out solutions	• Passive fail-safe system	• Prevents stuck tools
• Milling / Mechanical solutions	• Modular	• Maximized speed and force
• Seismic measurements	• Configurable	• Full surface read-out (SRO)
• Fluid sampling	• Logging while tractoring	• Maximum efficiency
• Fishing / Pipe recovery	• NACE compliant	• Optimal data acquisition
• SAGD ranging	• OH or CH applications	
• Depth determination		

Specifications*	Imperial	Metric
• Running OD nominal	• 2 1/2"	• 63,5 mm
• Weight in air	• 156.5 lbs – 253.5 lbs	• 71 Kg - 115 Kg
• Max speed	• 82 ft/min - 131 ft/min	• 25 m/min - 40 m/min
• Max pull force	• 1500 lbs	• 680 Kg
• Maximum well pressure	• 20,000 psi	• 137 MPa (1,379 bar)
• Maximum well temperature	• 266 °F	• 130 °C
• Tensile strength	• 60,700 lbs	• 270 kN
• Compressive strength	• 42,700 lbs	• 190 kN

\* Dependent upon configuration

